# Z L 1/2 C

# SELF CLOSE Tap Range Single Timed Flow Toggle Control Basin Pillar Tap 6lpm Chrome

#### **Features:**

- Toggle action
- 15 second time delay
- Supplied with 6 I/m flow regulator
- Supplied with cold and hot indices for flexibility
- •

## **Product Certifications:**

WRAS Certificate No: WRAS Expiry Date:



31/03/2020

1503950






For more products, visit our website:



Specification				
Style:	Contemporary			
Product Type:	Taps			
Finish/Colour:	Chrome			
Main Construction Material:	Brass			
Mount Type:	Deck			
Handle Type:	Toggle			
Connection Inlet:	1/2" BSP			
Number of Tap Holes Required:	1			
Valve/Cartridge Type:	Automatic Shut-Off Valve			
Plumbing System Suitability	All			
Working Pressure Range:	Min. 0.2 bar, Max. 3.0 bar			
Maximum Hot Water Temperature: °c	65			
Maximum Dynamic Pressure: (bar)	3			
Maximum Static Pressure: (bar)	10			
Flow Type:	Single Flow			
Flow Rate: (l/min @ 3 bar)	35.6			
Connection Outlet:				
Isolation Included:	No			

### **Dimensions (measurements in mm)**



Flow Rates (I/min)						
System Pressure (bar)	0.2	0.5	1	2	3	
With Flow Regulators	1.3	3.3	4.8	5.6	6.3	
Without Flow Regualtors	8.5	14.1	20.4	29	35.6	







Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 1SG. Telephone: 0844 701 6274. Facsimile: 0844 701 6275. Web Site: www.bristan.com Email: enquire@bristan.com. The information contained on this page was correct at date of issue. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuing improvement in design and performance of its products and so reserves the right to change specifications without prior notice.