COBALT SHWR PK2



Features:

- Integral two outlet diverter
- 200mm square fixed head with shower arm
- Single function handset and hose with integral handset holder and wall outlet

Product Certifications:

33.8 L/Mir

Specification	
Style:	Contemporary
Finish/Colour:	Chrome Plated
Main Construction Material:	Brass; ABS
No of Controls:	3
Shower Type:	Dual Control
Shower Head Type:	Fixed Head and Handset
Valve/Cartridge Type:	3/4" Ceramic Disc Valve 1/4 turn
Maximum Hot Water Supply Temperature ^o C:	65
Maximum Static Pressure: (bar)	10
Plumbing System Suitability:	Suitable for all plumbing systems
Working Pressure Range:	Min: 0.2 bar, Max: 5 bar
Connection Inlet:	15mm Compression
Connection Outlet:	G 1/2"
Isolation Valve Included:	No
Check Valve Included:	Yes



SHOWERS

D1

For more products, visit our website: Flow Rates (I/min) http <u>www.bristan.com</u> System Pressure (bar) 0.2 0.5 2 5 1 3 Outlet 1 6.9 12.8 19 27.6 33.8 43.6 Outlet 2 6.7 12.5 18.5 27 33 42.6 TECHNICAL DATA

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 ISG. Telephone: 0844 701 6274. Facsimile: 0844 701 6275. Web Site: www.bristan.com Email: enquire@bristan.com. The information contained on this page was correct at date of issue. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuing improvement in design and performance of its products and so reserves the right to change specifications without prior notice.